

HTK 14T

Suitable accessories

Spare wheel and bracket
 Duomatic coupling
 Towing eye Ø 50 mm
 Swivelling towing eye with Ø 40/50 mm towing eye
 Drawbar for different lengths and coupling heights
 7-pin socket at rear
 Reversing light (additional)
 Work light
 Rotating beacon incl. 7-pin socket
 LED rotating beacon
 Wear plate for bridge
 Hinged doors instead of tailgate
 Side wall extensions
 Steel grid extensions
 Plastic tool box
 Night parking warning signs
 Rear market boards
 Bridge safety supports
 Covering net
 Side impact protection
 Aluminium ramps
 Wide tyres



Side impact protection



Side panel lifting springs




Additional LED work light



Aluminium ramps



Additional reversing light



Plastic tool box

Additional accessories available on request

DETAILS

TANDEM THREE-WAY TIPPER 14t HTK 14T



HTK 14T Technical details

Model name	HTK 145524	HTK 145024
Total permissible weight in kg	14 400	14 400
Total dimensions in mm (LxWxH)	7 500 x 2 550 x 1 600	7 000 x 2 550 x 1 600
Internal dimensions in mm (L x W)	5 530 x 2 420	5 030 x 2 420
Load capacity in kg	10 250	10 400
Load height in mm	1 070	1 070
Tilt angle (side/rear) in degrees	45/48	45/48
Tyres	285/70 R19.5"	285/70 R19.5"

Subject to technical modifications. All dimensions are approximate values and refer to the standard vehicle without accessories. Additional equipment changes both the unladen weight and the load capacity!



HTK 14T
AND MORE



humbaur.com/en/trailer/
three-way-tipper/htk-14t

TANDEM THREE-WAY TIPPER 14t HTK 14T



Designed for the
highest level of
endurance and
variability

HTK 14T General equipment

CHASSIS

- Axles with drum brake, no-maintenance parabolic suspension for optimal load compensation

BRAKING SYSTEM

- Compressed air brake with release valve, automatic load-dependent ALB brake, connecting lines with couplings in red/yellow, brake system with spring-loaded parking brake

DRAWBAR SYSTEM

- Central bar with 40-mm-diameter screw towing eye, galvanised, can be infinitely adjusted via the crank handle

ELECTRICS

- 12/24-volt lighting system with multi-chamber rear lights and LED side marker lights
- 15-pin connector

LOADING + LOAD SECURING

- Lashing points 6 t set into the bridge floor (5 pairs / 5.0 m; 6 pairs / 5.5 m)

CHASSIS FRAME

- Solid, welded and galvanised frame for optimal stability and safety; bridge floor made of 4 mm fine-grain steel, non-interchangeable rocker bearings
- Motorised hydraulic three-way tipping system, five-level cylinder with lift limiter
- Mudguards with anti-spray

- 2 wheel chocks with holder
- Reinforced 12 t gear-supported jack with load and overdrive speed

TIPPER BRIDGE

- Laser-welded quality steel side walls 500 mm, can be folded down on the sides and at the back, removable and oscillating with central locking mechanism, removable front wall
- Bridge frame hot-dip galvanised with longitudinal, lateral and diagonal braces for exceptional stability and concentrated loads
- Optional: Side walls primed and lacquered with high-quality ZK paint for optimal corrosion protection, sealed hollow spaces, your choice of single-colour paint in RAL

Do you have any questions, or would you like a personal consultation?
We look forward to hearing from you!



Contact us by phone on **+49 (0)821 24 929 - 0**
or via email at lkw-anhaenger@humbaur.com



Find your dealer
or service partner now!
[humbaur.com/en/dealerservice/
dealer-search](https://humbaur.com/en/dealerservice/dealer-search)



Heavy loads made easy –
**HGV TRAILERS
FROM HUMBAUR**

- Easy to operate
- Lifelong use
- Safe transport
- Long-term savings



TANDEM THREE-WAY TIPPER HTK 14T

HIGH LIGHTS

With a permitted total weight of 14.4 metric tons, the HTK 14t can take precisely the extra load you need. It is best suited for towing vehicles over 7.49 metric tons. Despite the high total weight, you can use it with a 40 mm towing eye. These models impress most of all thanks to the generous dimensions of their undercarriage and tipping bridge frames. They set the bar for durability and reliability.



Manual central locking for side panels

Ingenious functionality down to the last detail



EASY TO OPERATE

- Draw tube adjustable without steps
- 15-pin connector
- Motorised hydraulic three-way tipper

LIFELONG USE

- Laser-welded high-quality steel side plates
- Reinforced 12 t gearbox support spool



Your heavy load benefit package
NOW STANDARD FOR ALL
HUMBAUR HGV TRAILERS



More information in this video
<https://www.youtube.com/watch?v=YSHii7PSIU>

