

STARTRAILER




MULTIFUNCTIONAL LIGHTING INTEGRATED IN THE UNDERRUN PROTECTION



13-PIN PLUG AND REVERSING LIGHTS




FIXED FRONT WALL



DROP SIDES MADE OF ANODIZED, DOUBLE-WALLED ALUMINIUM PROFILE WITH ROUND BUTTONS



TAILGATE WITH TENSION LOCKS



CORNER STANCHIONS WITH INSERT OPTIONS



TIE-DOWN EYES INTEGRATED IN THE SIDE WALLS



ALWAYS
A GOOD CHOICE



- Accessories** (optional)
- 1** Standard jockey wheel with mounting parts (for 251313 standard equipment)
 - Spare wheel
 - Spare wheel bracket
 - 2** Drop side extensions 300 mm
 - 3** Wheel shock absorbers for 251313 (without/with 100 km/h confirmation)
 - H-frame
 - 4** Tarpaulin and frame
Load height 1500 mm
 - 5** Flat cover

Permissible gross weight in kg	MODEL	Overall dimension in mm	Internal dimensions in mm	Load capacity in kg	Load height in mm	Tyres in inches	braked
750	STARTRAILER H 752513	3585 x 1760 x 800	2510 x 1310 x 300	602	500	13	
1300	STARTRAILER H 132513	3765 x 1800 x 830	2510 x 1310 x 300	1078	530	14	✓

Important safety information: The trailer may only be used with express adherence to all road traffic, professional association and load securing regulations. We assume no responsibility for printing or other errors or omissions. Subject to change without notice. Accessories only available separately. All dimensions are approximate values and refer to the standard vehicle without accessories. Printed in Germany. Reprint prohibited. Illustrations similar, some trailers show special equipment.