

PERFECT FOR THE IVECO EUROCARGO

FlexBox DRY

- > 30 mm sandwich panels
- Insulated roof fitted as standard
- Double-hinged rear doors
- Rear portal & auxiliary frame hot-dip galvanised
- LED interior lighting with motion detector
- Sliding tie-down points on the floor
- Step with handgrip at the rear
- Plastic mudguards with dirt collectors
- Lighting according to German Road Traffic Regulations (StVZO)

TUNNORD DE TUNNORD TUNNORD MOLTER TUNNER AC NO. TO TUNNER MOLTON

The FLEXBOX superstructures are checked by TÜV NORD according to Code XL.



FlexBox COOL

- ▶ 60 mm sandwich panels
- ▶ 65 mm insulated floor
- Double-hinged rear doors
- Auxiliary frame hot-dip galvanised, rear portal made of stainless steel
- LED interior lighting with motion detector
- Step with handgrip at the rear
- Plastic mudguards with dirt collectors
- Lighting according to German Road Traffic Regulations (StVZO)

Carrier aggregates, Konvekta, Mitsubishi and Thermo King

FlexBox FREEZE

- ▶ 80 mm front wall & roof
- ▶ 65 mm side wall panels
- ▶ 120 mm insulated floor
- ▶ 85 mm double-hinged rear doors
- Auxiliary frame hot-dip galvanised, rear portal made of stainless steel
- ► LED interior lighting with motion detector
- Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- Lighting according to German Road Traffic Regulations (StVZO)

Carrier aggregates, Konvekta, Mitsubishi and Thermo King





The FLEXBOX superstructures are certified in accordance with ATP and HACCP regulations.





PERFECT FOR THE IVECO EUROCARGO



FLEXBOX DRY	7,49 to		12 to		16 to	
Internal Dim. (L x W x H) in mm	6085 x 2485 x 2285	7285 x 2485 x 2285	6085 x 2485 x 2285	7285 x 2485 x 2285	6085 x 2485 x 2285	7285 x 2485 x 2285
Steel construction weight in kg	1250	1460	1300	1520	1360	1580
ALU construction weight in kg	980	1150	1030	1210	1090	1270
FLEXBOX COOL	7,49 to		12 to		16 to	
Internal Dim. (L x W x H) in mm	6070 x 2470 x 2465	7370 x 2470 x 2465	6070 x 2470 x 2465	7370 x 2470 x 2465	6070 x 2470 x 2465	7370 x 2470 x 2465
Steel construction weight in kg	1560	1830	1660	1950	1660	1950
ALU construction weight in kg	1215	1425	1315	1550	1315	1550
FLEXBOX FREEZE	7,49 to		12 to		16 to	
Internal Dim. (L x W x H) in mm	6020 x 2450 x 2370	7320 x 2450 x 2370	6020 x 2450 x 2370	7320 x 2450 x 2370	6020 x 2450 x 2370	7320 x 2450 x 2370
Steel construction weight in kg	1690	1970	1790	2100	1790	2100
ALU construction weight in kg	1320	1540	1420	1660	1420	1660

Important safety information: The vehicle may only be used with express adherence to all road traffic, professional association and load securing regulations. We assume no responsibility for printing or other errors or omissions. Subject to change without notice. All dimensions are approximate values and refer to the standard vehicle without accessories. Printed in Germany. Reprint prohibited · Illustrations similar, some trailers show special equipment · ATP, Code XL and HACCP certifications only in specific designs · As at: 08/18.